Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Section I – Product and Company Identification

Panther Boss Water Clear Knife Grade **Product Identifier:** Product Description/Use: Polyester Adhesive and Filler **Product Restrictions:** None Known **Product Code:** 01010 Chemical Family: Polyester Company: Stone Boss

24 Hour Emergency Telephone Number: **CHEMTREC 800-424-9300**

26-04 Borough Place Woodside, NY 11377 Phone: (201) 254-2450

Section II – Hazards Identification

GHS Hazard Classification(s): Flammable Liquid: Category 3 Acute Toxicity: Category 4, Inhalation Skin Irritation: Category 2 Eye Irritation: Category 2A Germ Cell Mutagenicity: Category 2 Carcinogenicity: Category 2 **Reproductive Toxicity:** Category 1B Aspiration Hazard: Category 1 Acute Aquatic Toxicity: Category 1 Specific Target Organ Systemic Toxicity - Single Exposure: Category 1, Central Nervous System Specific Target Organ Systemic Toxicity - Single Exposure: Category 3, Respiratory Tract Irritation Specific Target Organ Systemic Toxicity - Repeated Exposure: Category 1, Blood System, Liver, Nervous System, Respiratory tract/organ



Symbols:

Hazard Statements:

- H226: Flammable liquid and vapor.
- H304: Maybe fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H341: Suspected of causing genetic defects.
- H351: Suspected of causing cancer.

Precautionary Statements:

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

Signal Word(s): Danger

H360: May damage fertility or unborn child. H370: Causes damage to organs (Central Nervous System)

H372: Causes damage to organs (blood system, LIver, Nervous system, respiratory tract/organ) through prolonged or repeated exposure. H401: Toxic to aquatic life.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust/fume/gas/mist/vapor/spray. P264: Wash skin thoroughly after handling.

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.

Hazards not otherwise classified: None known.

Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u> Polyester Resin	<u>Synonym(s)</u> N/A	<u>% (By Weight)</u> 60-65%	<u>CAS#</u> N/A	<u>EINECS Nc.</u> N/A
Styrene	Phenylethene, Ethenyl benzene, Ethenylbenzene, Vinyl Benzene, Styrol,	30-35%	100-42-5	202-851-5
	Styrolene, Cinnamene, Cinnamenol, Cinnamol			
Hydrophobic Amorphous Fumed Silica	Hydrophobized Dispersed Silica, Synthetic Silica, X-ray Amorphous Silicon Dioxide	5-10%	67762-90-7	N/A

Section IV – First Aid Measures

If Swallowed: DO NOT INDUCE VOMITING (aspiration hazard). Seek immediate medical aid.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Consult a physician if any signs or symptoms described in this document occur. Wash contaminated clothing.

If Inhaled: Remove victim from exposure. If victim is unconscious, administer artificial respiration and/or oxygen as needed. Seek medical aid.

Eyes: Flush with copious amounts of water for 15 minutes. Seek immediate medical aid.

Most important symptoms/effects, acute and delayed:

Potential acute health effects:

Eye Contact:	Causes serious eye irritation.
Inhalation:	Harmful if inhaled. May cause respiratory irritation.
Skin Contact:	Causes skin irritation.
Ingestions:	No known significant effects or critical hazards.
exposure sign/syn	aptoms:

Over-exposure sign/symptoms:

Eye Contact:	Adverse symptoms may include the following: pain or irritation, watering, redness.
Inhalation:	Adverse symptoms may include the following: respiratory tract irritation, coughing.
Skin Contact:	Adverse symptoms may include the following: irritation, redness.
Ingestions:	Adverse symptoms may include the following: no specific data

Note to Physicians: Ingestion of this product or subsequent vomiting can result in aspiration of light hydrocarbon liquid which can cause pneumonitis. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section V - Fire Fighting Measures

Suitable Extinguishing Media: Water Spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Unsuitable Extinguishing Media: Do not use water jet.

Special Fire Fighting Procedures: Firefighters and others exposed to vapors or products of combustion should wear selfcontained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use. **Unusual Fire and Explosion Hazards:** At elevated temperatures, such as in a fire, polymerization may take place. If polymerization takes place in a closed container, there is the possibility of violent rupture of the container. Product vapors may form an explosive mixture in air.

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Hazardous Products of Combustion: Decomposition products may include the following material: carbon oxides, nitrogen oxides.

Other Remarks: Liquid and vapor may cause flash fire or ignite explosively. Vapor is heavier than air and may settle in low places or spread long distances to a source of ignition and flashback. Explosive atmospheres may linger. Closed containers can rupture and release toxic vapors or decomposition products.

Section VI - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

Methods and Materials for Containment and Cleaning Up

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section VII - Handling and Storage

Precautions for Safe Handling

Protective Measures: Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible materials, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Use explosion-roof electrical (ventilating, lighting and material handling) equipment. Use only on-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and con be hazardous. Do no reuse container.

Advice on General Occupational Health: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for Safe Storage, Including and Incompatibles: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information.

Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Section VIII - Exposure Controls/Personal Protection

Likely Routes of Exposure: Inhalation, Dermal, Ingestion. Control Parameters Occupational exposure Limits:

United States					_	Aust	tralia		
	OSHA-PEL		ACGIH-TLV		NIOSH-REL		SWA		VA
	TWA	Ceiling	TWA	STEL	TWA	STEL		TWA	STEL
Styrene	100 ppm	200/600 ppm*	20 ppm	40 ppm	50 ppm	100 ppm		50 ppm	100 ppm
Ethylbenzene	100 ppm	N/A	20 ppm	N/A	100 ppm	125 ppm		100 ppm	125 ppm

*200ppm; 600 ppm (Peak) for a single time period up to 5 minutes in any 3 hours.

Engineering Controls: Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures: Wash Hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. **Body Protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory Protection:** Use a properly fitted, air-purifying of air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section IX – Physical and Chemical Properties

Physical State: Paste like Color: Opaque White Odor: Aromatic, sweet

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Odor Threshold: 0.017~1.9 ppm (Detect) 0.15 ppm (Recognition) **pH:** Not Available Melting Point/Freezing Point: -23.8°F/-30.6°C (Styrene) Boiling Point: 293°F/145°C (Styrene) Boiling Range: Not Available Flash Point: Closed Cup: 88°F/31.1°C (Styrene) Burning Time: Not Applicable Burning Rate: Not Applicable **Evaporation Rate:** <1 (Butyl acetate) = 1) Flammability (solid, gas): Not Available Lower and Upper Explosive (Flammable) Limits: Lower: 1.1% Upper: 6.1% Vapor Pressure: 4.3 mm Hg (0.57 kPa) @ 68°F/20°C (Styrene) Vapor Density: 3.6 (Air = 1) (Styrene) Relative Density: 1 to 1.2 (Water = 1) Solubility: Immiscible in water Partition Coefficient: n-Octanol/water : Not Available Auto-Ignition temperature: 914°F/490°C **Decomposition Temperature:** Not Available SADT: Not Available Viscosity: Not Available. Molecular Weight: 10,000-15,000

Section X - Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: Material is stable

Hazardous Polymerization: Yes

Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. **Incompatibility (materials to avoid):** Strong acids and oxidizing agents

Hazardous Decomposition: Heating of this material to decomposition may cause the emission of irritating, acrid fumes. Under normal storage conditions and use, hazardous decomposition products should not be produced.

Section XI - Toxicological Information

Acute l'oxicity:					
Product/Ingredient Name	<u>Result</u>	Species		<u>Dose</u>	Exposure
Styrene	LC50 Inhalation Gas	Rat		2770 ppm	4 hours
	LC50 Inhalation Vapor	Rat		11,800 mg/m ³	4 hours
	LD50 Oral	Rat		2,650 mg/kg	-
Irritation/Corrosion:					
Product/Ingredient Name	<u>Result</u>	Species	<u>Score</u>	<u>Dose</u>	Observation
Styrene	Eyes - Mild Irritant	Human	-	50 ppm	-
	Eyes - Moderate Irritant	Rabbit	-	24 hours-100 mg	-
	Eyes - Severe Irritant	Rabbit	-	100 mg	-
	Skin - Mild Irritant	Rabbit	-	500 mg	-
	Skin - Moderate Irritant	Rabbit	-	100%	-
Conditionation, Not available					

Sensitization: Not available Mutagenicity: Not available

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Carcinogenicity: Not available

Conclusion/Summary: Styrene manufacturers have determined that the GHS Hazard Classification criteria has not been met.

Classification:

Product/Ingredient Name	<u>OSHA</u>	<u>IARC</u>	<u>NTP</u>
Styrene	-	2B*	Reasonably anticipated to be a human carcinogen.

* The International Agency for Research on Cancer (IARC) has classified styrene as possibly carcinogenic to humans (class 2B). The IARC 2B classification is not based on significant new evidence that styrene might be a carcinogen, but on a revised IARC classification scheme and new data on styrene oxide. The Styrene Information and Research Center does not agree with the reclassification and has published the following statement: "Recently published studies tracing 50,000 workers exposed to high occupational levels of styrene over a period of 45 years showed no association between styrene and cancer, no increase in cancer among styrene workers (as opposed to the average among all workers), and no increase in mortality related to styrene."

Reproductive Toxicity: Not available

Teratogenicity: Not available

Specific Target Organ Toxicity (Single Exposure): Not available

Specific Target Organ Toxicity (Repeated Exposure): Not available

Aspiration Hazard: Not available

Likely Routes of Exposure: Inhalation, Dermal, Ingestion.

Potential Acute Health Effects:

Eye Contact: Causes serious eye irritation. Inhalation: Harmful if inhaled. Skin Contact: Causes skin irritation. Ingestion: Irritating to mouth, throat and stomach.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics:

Eye Contact: Adverse symptoms may include the following - Pain or Irritation. Watering. Redness. Inhalation: No specific data.

Skin Contact: Adverse symptoms may include the following - Irritation. Redness.

Ingestion: No specific data.

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Expousres:

Short Term Exposures:

Potential Immediate Effects: Not available.

Potential Delayed Effects: Not available.

Long Term Exposures:

Potential Immediate Effects: Not available.

Potential Delaved Effects: Not available.

Potential Chronic Health Effects: Not Available.

General: Not available.

Carcinogenicity: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental Effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Acute Toxicity Estimates

Route	ATE Value
Oral	2,650.8 mg/kg
Inhalation (gases)	2,770.9 ppm
Inhalation (vapors)	11.8 mg/l

Section XII - Ecological Information

TOXICITY:			
Product/Ingredient Name	<u>Result</u>	<u>Species</u>	Exposure
Styrene	Acute EC50 1400 µg/l Fresh Water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 720 µg/l Fresh Water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 4700 µg/l Fresh Water	Daphnia - Daphnia magna	48 hours
	Acute LC50 13000 µg/l Fresh Water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 4020 µg/l Fresh Water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 63 µg/l Fresh Water	Algae - Pseudokirchneriella subcapitata	96 hours

Persistence and Degradability: Not Available

Bioaccumulative Potential:			
Product/Ingredient Name	<u>LogPow</u>	<u>BCF</u>	Potential
Styrene	0.35	13.49	low

Mobility in Soil:

Soil/water Partition Coefficient (Koc): Not available Other Adverse Effects: No known significant effects or critical hazards.

Section XIII - Disposal Considerations

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

Special Precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do no cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soul, water ways, drains and sewers.

Section XIV - Transportation Information

DOT (DEPARTMENT OF TRANSPORTATION) Technical Name: Resin Solution Hazard Class: 3 NA/UN Number: 1866 Packing Group: III

Canada (TDG)

Technical Name: Resin Solution Hazard Class: 3 NA/UN Number: 1866 Packing Group: III

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Marine Pollutant: No Please refer to DOT regulations for more info

Please refer to TDG Regulations for more info

International Air Transport Association (IATA)	International Maritime Organization (IMO)
Technical Name: Resin Solution	Technical Name: Resin Solution
Hazard Class: 3	Hazard Class: 3
NA/UN Number: 1866	NA/UN Number: 1866
Packing Group: III	Packing Group: III
ERG Code: 3L	EmS: F-E, S-E
Marine Pollutant: No	Marine Pollutant: No
Please refer to IATA regulations for more info.	Please refer to IMO regulations for more info.

Special Precautions for User: Transport within users premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.

Section XV - Regulatory Information

United States Federal Regulations:

Sara Title III - Section 311/312 Criteria Immediate (Acute) Health E Chronic (Delayed) Health Ef Fire Hazard: Sudden Release of Pressure Reactivity:	ffects: fects:	<u>Yes/No</u> Yes Yes No No		
Sara Title III - Section 313 <u>Criteria</u> Form R - Reporting	<u>Product/Ingredie</u> Styrene	ent Name	<u>CAS Number</u> 100-42-5	<u>%</u> 30-35
Requirements Supplier Notification	Styrene		100-42-5	30-35

State Regulations:

Massachusetts: The following components are listed: Styrene Monomer New York: The following components are listed: Styrene

New Jersey: The following components are listed: Styrene Monomer

California: SCAQMD Rule 1162 establishes specific process, control, housekeeping, and recordkeeping requirements for fabrication operations using polyester resin materials. It is the responsibility of the fabricator to ensure compliance with these requirements.

WARNING – This product can expose you to chemicals including Styrene & Ethylbenzene, which are known to the state of California to cause cancer. For more information go to <u>www.P65Warnings.ca.gov</u>

Section XVI - Other Information

Hazardous Material Information System (United States):


Health	2
Flammability	3
Physical Hazards	1

Company Name: Stone Boss **Product Name: Panther Boss Water Clear Knife Grade** Issue Date: 8/23/10 Revision Date: 8/12/19 SDS Number: 237-01010

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Asociation (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (United States):



Reprinted with permission from NFPS 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPS 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.