

Tel. +49(0)911-642960 Fax. +49(0)911-644456

e-mail info@akemi.de

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· Trade name: Anti-Slide R9

Article number: 11861, 11862, 11864, 11865
 UFI: 8CU1-80U7-W00W-QPR7

1.2 Relevant identified uses of the substance or mixture and

uses advised againstNo further relevant information available.

· Application of the substance / the

<u>mixture</u> Discharging agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Lechstrasse 28 D 90451 Nürnberg

· Further information obtainable

<u>from:</u> Laboratory

1.4 Emergency telephone

<u>number:</u> Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.





GHS05 GHS07

· Signal word Danger

· Hazard-determining components of

<u>labelling:</u> ammonium bifluoride

Alcohols, C13-C15 branched and linear, ethoxylated

phosphoric acid ammonium fluoride

· <u>Hazard statements</u> H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary statements P101 If medical advice is needed, have product container or label at

hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face

protection/hearing protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel

unwell.

(Contd. on page 2)



Page 2/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 1)

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/

regional/national/international regulations.

· Additional information: Contains biocidal products: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-

one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:

1), 2-methyl-2H-isothiazol-3-one

· 2.3 Other hazards

· Results of PBT and vPvB assessment

 $\begin{array}{ccc} \cdot & \underline{\mathsf{PBT:}} & & \mathsf{Not} \ \mathsf{applicable.} \\ \cdot & \mathsf{vPvB:} & & \mathsf{Not} \ \mathsf{applicable.} \end{array}$

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|---|------|
| CAS: 1341-49-7 EINECS: 215-676-4 Index number: 009-009-00-4 Reg.nr.: 01-2119489180-38-xxxx | ammonium bifluoride Acute Tox. 3, H301 Skin Corr. 1B, H314 Specific concentration limits: Skin Corr. 1B; H314: $C \ge 1$ % Skin Irrit. 2; H315: 0.1 % $\le C < 1$ % Eye Irrit. 2; H319: 0.1 % $\le C < 1$ % | <10% |
| CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx 02-2119751533-40-0000 | 2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319 | 1-5% |
| CAS: 157627-86-6 EC number: 935-523-1 Reg.nr.: 02-2119548515-35-0000 | Alcohols, C13-C15 branched and linear, ethoxylated Eye Dam. 1, H318 Acute Tox. 4, H302 Aquatic Chronic 3, H412 | 1-5% |
| CAS: 7664-38-2 EINECS: 231-633-2 Index number: 015-011-00-6 Reg.nr.: 01-2119485924-24 | phosphoric acid Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1B; H314: $C \ge 25$ % Skin Irrit. 2; H315: 10 % $\le C$ < 25 % Eye Irrit. 2; H319: 10 % $\le C$ < 25 % | 1-5% |
| CAS: 12125-01-8 EINECS: 235-185-9 Index number: 009-006-00-8 | ammonium fluoride Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 | <1% |
| Additional information: | For the wording of the listed hazard phrases refer to section 16. | |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

(Contd. on page 3)



Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

· After inhalation: Supply fresh air.

(Contd. of page 2)

transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

No further relevant information available.

doctor.

· After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Formation of toxic gases is possible during heating or in case of fire.

In case of unconsciousness place patient stably in side position for

• 4.2 Most important symptoms and effects, both acute and

delayed 4.3 Indication of any immediate

medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> CO2, powder or water spray. Fight larger fires with water spray or alcohol

resistant foam.

5.2 Special hazards arising from

the substance or mixture

5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Mount respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures
 6.2 Environmental precautions:
 Wear protective equipment. Keep unprotected persons away.
 Do not allow product to reach sewage system or any water course.

b.2 Environmental precautions: Do not allow product to reach sewage system of any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 3)

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by

storerooms and receptacles: Provide acid-resistant floor.

· Information about storage in one

common storage facility: Do not store together with oxidising and acidic materials as well as heavy-metal

compounds.

· Further information about storage

conditions:

Protect from frost.

Keep container tightly sealed.

· Storage class: 8 B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

| <u> </u> | itror parameters | |
|---|-------------------------------------|--|
| · Ingredients with limit values that require monitoring at the workplace: | | |
| 112-34-5 2-(2-butoxyethoxy)ethanol | | |
| IOELV Short-term value: 101.2 mg/m³, 15 ppm | | |
| | Long-term value: 67.5 mg/m³, 10 ppm | |
| 7664-38-2 phosphoric acid | | |
| IOELV | Short-term value: 2 mg/m³ | |
| | Long-term value: 1 mg/m³ | |

· DNELs

1341-49-7 ammonium bifluoride

| Oral | DNEL (Kurzzeit-akut) | 0.015 mg/kg bw/day (BEV) |
|------------|----------------------------|--------------------------|
| | DNEL (Langzeit-wiederholt) | 0.015 mg/kg bw/day (BEV) |
| Inhalative | DNEL (Kurzzeit-akut) | 3.8 mg/m³ Air (ARB) |
| | DNEL (Langzeit-wiederholt) | 2.3 mg/m³ Air (ARB) |
| | | 0.045 mg/m³ Air (BEV) |

112-34-5 2-(2-butoxyethoxy)ethanol

| Oral | | DNEL (Langzeit-wiederholt) | 5 mg/kg bw/day (BEV) |
|--------|------|-----------------------------|-----------------------|
| Derma | al | DNEL (Langzeit-wiederholt) | 83 mg/kg bw/day (ARB) |
| | | | 50 mg/kg bw/day (BEV) |
| Inhala | tive | DNEL (Kurzzeit-akut) | 101.2 mg/m³ Air (ARB) |
| | | | 7.5 mg/m³ Air (BEV) |
| | | DNEL (Langzeit-wiederholt) | 67.5 mg/m³ Air (ARB) |
| | | | 40.5 mg/m³ Air (BEV) |

7664-38-2 phosphoric acid

| Dermal | DNEL (Langzeit-wiederholt) | 0.1 mg/kg bw/day (BEV) |
|----------|-----------------------------|---------------------------|
| Inhalati | ve DNEL (Kurzzeit-akut) | 2 mg/m³ Air (ARB) |
| | DNEL (Langzeit-wiederholt) | 1-10.7 mg/m³ Air (ARB) |
| | | 0.36-4.57 mg/m³ Air (BEV) |

· PNECs

1341-49-7 ammonium bifluoride

PNEC (wässrig) 76 mg/l (KA)
1.3 mg/l (SW)

PNEC (fest) 22 mg/kg Trockengew (BO)

(Contd. on page 5)



Page 5/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 4)

| 112-34-5 2- | (2-butoxyet | noxy)etnand |
|-------------|-------------|-------------|
| | | |

PNEC (wässrig) 200 mg/l (KA)

0.11 mg/l (MW) 1.1 mg/l (SW) 3.9 mg/l (WAS)

PNEC (fest)

0.32 mg/kg Trockengew (BO) 0.44 mg/kg Trockengew (MWS) 4.4 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic

measures:

Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

Hand protection

After use of gloves apply skin-cleaning agents and skin cosmetics.

Skin protection agent recommendation for preventive skin shelter without use of

protective gloves:

STOKODERM (http://www.stoko.com)

Skin protection agent recommendation for preventive skin shelter in application

and combination of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

FRAPANTOL (http://www.stoko.com)

Skin protection agent recommendation for skin aftercare:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation

(Contd. on page 6)



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 5)

the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell,

internet: http://www.kcl.de).

· Material of gloves Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior

to the application.

· Penetration time of glove material Value for the permeation: Level ≤ 6, 480 min

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are

suitable:

Nitrile rubber, NBR

Camatril (KCL, Art No. 730, 731, 732, 733)

Fluorocarbon rubber (Viton) Vitoject (KCL, Art_No. 890) Butyl rubber, BR

Butoject (KCL, Art No. 897, 898)

· As protection from splashes gloves made of the following materials are

suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Chloroprene rubber, CR

Camapren (KCL, Art No. 720, 722, 726)

· Not suitable are gloves made of

the following materials:

Natural rubber, NR Leather gloves Strong material gloves

· Eye/face protection

Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless · Odour: Characteristic · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range 100 °C

Not applicable. · Flash point: · Ignition temperature: 225 °C

· pH at 20 °C

· Viscosity:

· Kinematic viscosity at 20 °C 11 s (DIN 53211/4) Not determined. · Dynamic:

Solubility

Not miscible or difficult to mix. · water:

· Vapour pressure at 20 °C: 23 hPa

(Contd. on page 7)



Page 7/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 6)

Density and/or relative density

Density at 20 °C: 1.04 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· <u>Auto-ignition temperature:</u> Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

· Solvent content:

• Organic solvents:
 • Water:
 • Solids content:
 5.0 %
 84.0 %
 11.6 %

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

Gases under pressure
Flammable liquids
Flammable solids
Void

· Self-reactive substances and mixtures

Void

Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

Void

· Substances and mixtures, which emit flammable

gases in contact with water

Void

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
 Thermal decomposition / conditions to be avoided:

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

<u>reactions</u> Reacts with alkali and metals.

Reacts with strong oxidising agents. Reacts with metals forming hydrogen. No further relevant information available.

10.4 Conditions to avoid
 10.5 Incompatible materials:
 10.6 Hazardous decomposition

No further relevant information available.

products: Phosphorus oxides (e.g. P2O5)

Irritant gases/vapours

(Contd. on page 8)



Page 8/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 7)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| · Acute toxicity | | Harmful if swallowed. |
|--------------------------------|-------------------------------|--------------------------|
| · <u>LD/LC50</u> \ | ∕alues rele\ | vant for classification: |
| ATE (Acu | te Toxicity | Estimates) |
| Oral | LD50 | >1,667-1,777 mg/kg |
| Dermal | LD50 | 108,578 mg/kg |
| Inhalative LC50/4 h 1,086 mg/l | | 1,086 mg/l |
| 1341-49-7 | 1341-49-7 ammonium bifluoride | |
| Oral | LD50 | 130 mg/kg (rat) |
| Inhalative | LC50/1h | 342 mg/l (mouse) |
| | | 1,276 mg/l (rat) |

112-34-5 2-(2-butoxyethoxy)ethanol

| Oral | LD50 | 2,410 mg/kg (mouse) (OECD 401) |
|--------|------|--------------------------------|
| | | >2,000 mg/kg (rat) |
| Dermal | LD50 | 2,764 mg/kg (rbt) (OECD 402) |

157627-86-6 Alcohols, C13-C15 branched and linear, ethoxylated

| Oral | LD50 | >500-2,000 mg/kg (rat) |
|--------|----------|----------------------------|
| Dermal | LD50 | >2,000 mg/kg (rat) |
| | LC50/48h | 1-10 mg/l (Oncorhynchus my |

7664-38-2 phosphoric acid

| Oral | LD50 | 1,250 mg/kg (rat) |
|------------|---------|----------------------|
| | | ≥410 mg/kg (rat) |
| Dermal | LD50 | 2,740 mg/kg (rabbit) |
| Inhalative | LC50 | 850 mg/l (rat) |
| | LC50/1h | 1.69 mg/l (rat) |

12125-01-8 ammonium fluoride

| Oral | LD50 | 100 mg/kg (ATE) |
|------------|----------|-----------------|
| Dermal | LD50 | 300 mg/kg (ATE) |
| Inhalative | LC50/4 h | 3 mg/l (ATE) |

· Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

Based on available data, the classification criteria are not met. · Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 9)



Page 9/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 8)

SECTION 12: Ecological information

| · 12.1 Toxicity | | | | |
|-----------------------|---|--|--|--|
| · Aquatic toxic | · Aquatic toxicity: | | | |
| 1341-49-7 a | 1341-49-7 ammonium bifluoride | | | |
| EC50 2,394 mg/l (BES) | | | | |
| LC100/96h | 562 mg/l (Brachydanio rerio) | | | |
| LC0/96h | 237 mg/l (Brachydanio rerio) | | | |
| EC10 | 1,317 mg/l (BES) | | | |
| | 2-butoxyethoxy)ethanol | | | |
| EC50/24h | 2,850 mg/l (daphnia magna) (DIN 38412) | | | |
| EC50/96h | >100 mg/l (Desmodesmus subspicatus) | | | |
| | >100 mg/l (Scenedesmus subspicatus) | | | |
| EC10/16h | 1,170 mg/l (pseudomonas putida) | | | |
| EC5 | 73 mg/l (Entosiphon sulcatum) | | | |
| EC50/48h | >100 mg/l (daphnia magna) (EU method C.2) | | | |
| ErC50/72h | 1,101 mg/l (Pseudokirchneriella subcapitata) (OECD 201) | | | |
| NOEC | >100 mg/kg (Desmodesmus subspicatus) | | | |
| EC10 | >1,995 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung) | | | |
| EC50/72h | >100 mg/l (Desmodesmus subspicatus) | | | |
| LC50/96h | 1,300 mg/l (lepomis macrochirus) (OECD 203) | | | |
| | >100 mg/l (Leuciscus idus) | | | |
| | 1,150 mg/l (poecilia reticulata) | | | |
| | Alcohols, C13-C15 branched and linear, ethoxylated | | | |
| EC50/48h | 1-10 mg/l (daphnia magna) | | | |
| EC10 | >1,000 mg/l (BES) | | | |
| EC50/72h | 1-10 mg/l (Scenedesmus subspicatus) | | | |
| | hosphoric acid | | | |
| EC50 | 270 mg/l (BES) | | | |
| | 270 mg/l (bacteria) | | | |
| EC50/48h | >100 mg/l (daphnia magna) (OECD 202) | | | |
| | 100 mg/l (Desmodesmus subspicatus) (OECD 201) | | | |
| EC50/72h | >100 mg/l (Desmodesmus subspicatus) (OECD 201) | | | |
| LC50/96h | 138 mg/l (Gambusia affinis) | | | |
| | 98-106 mg/l (lem) | | | |
| | 3-3.25 mg/l (lepomis macrochirus) | | | |

12.2 Persistence and

degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

12.6 Endocrine disrupting

<u>properties</u>

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 10)

ni pago ii



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 9)

· 12.7 Other adverse effects

- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow undiluted product or large quantities of it to reach ground water,

water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous

for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

| · European waste catalogue | |
|----------------------------|---|
| 16 00 00 | WASTES NOT OTHERWISE SPECIFIED IN THE LIST |
| 16 10 00 | aqueous liquid wastes destined for off-site treatment |
| 16 10 01* | aqueous liquid wastes containing hazardous substances |

Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

SECTION 14: Transport information

| · 14.1 UN number or ID number | |
|-------------------------------|--------|
| · ADR, IMDG, IATA | UN3265 |

· 14.2 UN proper shipping name

· ADR 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(AMMONIUM HYDROGENDIFLUORIDE)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(AMMONIUM HYDROGENDIFLUORIDE)

· 14.3 Transport hazard class(es)

· ADR



· Class · Label 8 (C3) Corrosive substances. 8

· IMDG, IATA



· <u>Class</u> 8 Corrosive substances.

· Label 8

14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 10)

• 14.6 Special precautions for user Warning: Corrosive substances.

<u>Hazard identification number (Kemler code):</u>
 <u>EMS Number:</u>
 Segregation groups

80
F-A,S-B
(SGG1) Acids

· Stowage Category

· Stowage Code SW2 Clear of living quarters.

Segregation Code
 SG36 Stow "separated from" SGG18-alkalis.
 SG49 Stow "separated from" SGG6-cyanides

· 14.7 Maritime transport in bulk according to IMO

<u>instruments</u> Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code E

·IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· <u>UN "Model Regulation":</u> UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(AMMONIUM HYDROGENDIFLUORIDE), 8, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances -

ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3, 55, 65

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 12)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.12.2022 Version number 2 (replaces version 1) Revision: 19.12.2022

Trade name: Anti-Slide R9

(Contd. of page 11)

· National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· <u>VOC EU</u> 51.8 g/l

15.2 Chemical safety

<u>assessment:</u> A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:
 Contact:
 Laboratory
 Elke Hake

Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de

· Date of previous version: 19.12.2022

· Version number of previous

version:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European

Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

ΕU